Tablet Locker

Specifications



In many organizations, shared portable devices, such as tablets, are prone to being lost, damaged, mislaid or stolen.

Our Tablet Locker solutions enable businesses to protect their technology and intellectual property better while gaining complete visibility and improving critical processes.

Our unique RFID technology ensures you always have full visibility of your equipment.

Charging facilities can be added to ensure tablets are fully charged before being issued to personnel.

Traka's Tablet Lockers enable you to secure, audit and manage your valuable technology investment, resulting in 100% user accountability, better utilization and significantly reduced loss or damage.



General features

- Available in two stack sizes, TL-20 with 20 compartments and TL-30 with 30 compartments
- Secure storage and management for up to 30 tablets per locker stack
- Tablets are readily available 24/7 to authorized users only
- Full audit trail of users and equipment transactions
- 7" capacitive touch screen for accurate input
- Easy access via a wide range of identification methods

Standalone features

- Operates entirely independently of your IT system with no network, PC or external connection required
- USB port for import/export of reports via flash drive
- Automatic data back up to removable SD card

Network features

 Full network capability and management through TrakaWEB

- Centralized administration and reporting
- Browser based allowing for remote administration
- Integrate with existing access control and third-party systems to provide centralized control and visibility

Optional features

- Compartments available as simple storage, with or without
- RFID detection and/or integrated chargingLocker stack can be expanded to form a system with up to 100 compartments

Specifications

Stack data	
Height (overall) ¹ :	TL-20 & TL-30 - 1720 mm / 67.7 in
Width (overall):	TL-20 & TL-30 - 631 mm / 24.8 in
Depth (overall):	TL-20 & TL-30 - 385 mm / 15.2 in
Weight (empty):	TL-20 - 88 kgs / 194 lbs; TL-30 - 93 kgs / 205 lbs
Additional information:	TL-20 has a storage compartment, whereas TL-30 uses this space for the extra smartphone compartments.

¹Overall height includes a sloping top.

Compartment data	
Height (internal):	TL-20 & TL-30 - 35 mm / 1.4 in
Width (internal):	TL-20 & TL-30 - 260 mm / 10.3 in
Depth (internal):	TL-20 & TL-30 - 290 mm / 11.4 in
No. compartments per stack	TL-20 - 20; TL-30 - 30
Max. compartments per system	Up to 100 per Touch controller

Material data	
Cabinet material:	Zintec steel
Color:	Standard frames are RAL7021 (black grey) and doors RAL9003 (signal white). Other RAL colors are available upon request.
Door material:	Perforated metal

Electrical data	
Power supply:	Input: 100-240V AC; Output: 15V DC
Battery backup:	DC12V 7Ah
Power supply rating (without charging):	35W (max) with or without RFID
Power supply rating (with charging):	As above plus electrical load of 355W per stack in each system
Device charging connection options:	A single USB-A connector is provided in each compartment.

Environmental data	
Operating temp:	Ambient, for indoor use only (-5°C to +40°C / +23°F to +104°F at 95% non-condensing relative humidity)

Installation data	
Mounting:	Not suitable for freestanding applications. Must be securely fixed to a load bearing wall.

Network & connectivity data	
Communications:	Ethernet (AES-256 encryption)
Reader interface options:	Clock/data, Wiegand, Serial (RS232/TTL) PIN only, OSDP Readers (RS485) with or without Encryption
Alarm interface:	x3 2A/30V DC max. rated relay contacts for connecting to alarms, access control systems, CCTV, etc.

Conformity & standards data	
Certifications:	CE (Including ROHS)
Approvals:	FCC (EMC); CSA; ICES (EMC)
Standards:	IS9001; ISO14001; ISO27001
Environmental:	NRTL (MET)

For more information on Traka and the benefits of intelligent lockers, please visit traka.com

traka.com

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.